


IPERMAXI ACCESSORI




- 1 Kit Led con Batteria / Kit Led with Battery
- 2 Kit Led / Kit Led
- 3 Riscaldatore Infrarossi 1500 watt IP X5 waterproof
Infrared Heater 1500 watt IP X5 waterproof
- 4 Kit Audio / Kit Audio
- 5 Pannelli laterali di chiusura cm H 240 in tessuto e finestra in cristal trasparente cm H 120 predisposti con velcro di cm 5
Lateral enclosures cm H 240, acrylic material or PVC, with crystal windows cm H 120. Velcro cm 5 included.

SPECIFICHE TECNICHE




CM.	900x900	1000x1000	1000x900	1100x900
A	495	495	495	525
B	340	340	340	320
C	60	60	65	65
D	730	760	760	760


Misure indicative soggette a variazioni senza preavviso



1000x900 cm. 33x30 ft
1100x900 cm. 36x30 ft



1000x1000 cm. 33x33 ft



900x900 cm. 30x30 ft


COLORE STRUTTURA ALLUMINIO



Telescopico

DETTAGLI/DETAILS

PALO/SHAFT	ALLUMINIO Ø 200 mm./ALUMINIUM Ø 200 mm.
STECHE/RIBS	ALLUMINIO mm. 100x30 CON RINFORZI/ALUMINIUM mm. 100x30 REINFORCED
TRATTAMENTO ACCIAIO/STEEL COATING	ZINCATURA + VERNICI TERMOINDURENTI/GALVANIZED + THERMOSETTING POWDER PAINTS
TRATTAMENTO ALLUMINIO/ALUMINIUM COATING	VERNICI TERMOINDURENTI/THERMOSETTING POWDER PAINTS
BULLONERIA/BOLTS, SCREWS	INOX/STAINLESS STEEL
MANTOVANA/VALANCE	DISPONIBILE/AVAILABLE
APERTURA/CHIUSURA/OPENING/CLOSING	ARGANO CON VITE SENZA FINE/WINCH
PESO KG./WEIGHT KG.	300 ca/300 approx



Base per zavorra
Base for ballast
105x118 cm.
Kg. 240



Zavorra per base
Ballast for bse
Kg. 60
cm. 50x50x10



Base da cementare
Inground base
cm. 40x40